

TraceSpanTM has leveraged patent-pending technology to provide innovative and unique solutions for the monitoring and recording of data across ADSL broadband networks. The Company's flagship product, $DSL \ Xpert^{TM}$, has broken new ground as the first non-intrusive performance-analysis solution for ADSL networks. Empowered by host-based signal processing, $DSL \ Xpert^{TM}$ monitors the transfer of all data between the central office (CO) and customer premise equipment (CPE).


By further leveraging of our core technology, TraceSpan has developed the DSL $Phantom^{TM}$ Lawful Interception (LI) monitoring solution. DSL $Phantom^{TM}$ is a monitoring device that records and stores broadband digital information, offering unique advantages for Law Enforcement Authorities (LEA) looking to capture any data between the central office and the target.

DSL PhantomTM operates on a powerful platform that supports high bit rates, enabling it to monitor information more effectively. DSL PhantomTM can be installed at virtually any location (Central Office or Street), while the data can be monitored at a remote location. DSL PhantomTM is completely non-intrusive, allowing the law enforcement agency to monitor information without being detected.


DSL Phantom[™] Advantages

- Non-Intrusive
- No effect on user in case of power outage or disconnection of monitoring equipment
- System does not contain ADSL chipset eliminating interoperability issues
- Capable of monitoring any activity including P2P
- Installed and operated with minimal number of people involved

- Easy to install and maintain
- Supports ADSL and future generation ADSL2 and ADSL2+ protocols (Annex A and Annex B models available)
- Simultaneous extraction of upstream and downstream data including time stamp
- Generic interface to mediation device
- Low power



Central Office (CO) Solution



Remote Site Solution

Specifications

Dimensions of LI Box	 Height - 2" (50mm) Width - 10.8" (275mm) Depth - 14.7" (375mm) Weight - 4.4lbs (2Kg)
Certification	■ CE
Power Supply	External power supplyVoltage I 10-240VACFrequency 50/60 HzPower 10W
Standards Supported	 G.992.1 (ADSL) G.992.3 (ADSL2) G.992.5 (ADSL2+) ANSI (T1.413) ETSI
Intercepted data	Save on Hard Disk

© 2004-2011 TraceSpan Communications Ltd. All rights reserved.

TraceSpan and DSL PhantomTM are trademarks of TraceSpan Communication Ltd.

All information correct at time of print. Product design & specifications are subject to change without notice.



E-mail: info@tracespan.com Website: www.tracespan.com

