

FEATURES / BENEFITS

- √ Interfaces V.35, RS-530, RS-422/449, RS-232, X.21 or TTL
- √ Network Simulation delays of 0, 5mS up to 1 second each direction
- √ Data Rates -Synchronous 300bps to 1.024Mbps
- ✓ Controls for RTS/CTS delay, DSR, DTR on a per port basis
- √ Status LED's for each port allows ease of connection and trouble shooting
- √ Timing Internal or external depending on model ordered
- √ 110/220VAC switch selectable
- √ Sturdy Metal Enclosure

DESCRIPTION

The UDC-RDS allows users to test/stage critical low data rate testing of DCE or DTE equipment while simulating network delay times. The unit provides a realistic simulation of physical network behavior with respect to time delays, clock rates and interface control signal passage. The unit supports user data rates of 300bps up to 1.024Mbps while providing delays from zero to a maximum of 1 second on each way per physical data link.

By using the UDC-RDS in place of or in series with a real data link (WAN) a wide variety of error conditions can be introduced under controlled and testable conditions.

The unit has two data port interfaces that support RS-232, RS-422/449, RS-530, V.35 and X.21. The data interfaces can be mix and matched where applicable, such as a V.35-to-RS-530 connection.

The UDC-RDS also allows the user to pass or force control signals. The control signals are also delayed along with the user data.

The unit is configured via accessible front panel dip switches and is available in a stand-alone or rack mount chassis. The user has no software to load as all configuration is within the UDC-RDS. Installation is fast and simple by setting the internal switches for Delay Simulation, Clocking, Carrier Operation and RTS to CTS delay. All clocking and signal crossover are provided within the UDC-RDS.

The UDC-RDS has status LED's for each attached DTE or DCE device which allows the user to visually confirm the presence of control signals.

The UDC-RDS is housed in a sturdy metal enclosure and operates on 110/220VAC.

The unit has a three year warranty and a 24 hour turnaround on warranty repairs.

EAST COAST DATACOM, INC.

SPECIFICATIONS

Application

Interconnection of two Routers or DTE (Terminal) devices located within proximity of each other while simulating network delays times

Simulation Delay Times

0, 5 milliseconds(mS) to approximately 1 second in 5mS increments each direction

Note: Baud Rate affects delay times(see manual chart)

Capacity

Two (2) Routers or DTE's /DCE's

Data Rates

300bps to 1.024Mbps

Data Channel Interfaces

Available in V.35, RS-530, RS-422/449, RS-232, X.21 or TTL

Surge Protection

Main power supply

Regulatory Approvals

UL 60950-1, 2nd Ed 2007; CAN/CSA 22.2 No. 60950-1-07; EN 60950-1:2006; EN 55022:2006; FCC Pt 15/ICES-003 Class A

Power Source

100-120 to 200-220VAC @10%, 50/60Hz, 0.16/0.08A, external 110/220 volt select switch, IEC Power Inlet, (2) 5mm Fuses

Environmental

Operating Temperature....32° to 122° F (0° to 50° C) Relative Humidity......5 to 95% Non-Condensing Altitude......0 to 10,000 feet

Dimensions

Height 1.75 inches (4.44 cm) Width 9.00 inches (22.86 cm) Length 9.0 inches (22.86 cm)

Weight

2 pounds (0.914Kg)

Warranty

Three Years, Return To Factory

ORDERING INFORMATION

Internal Clock Version

PT# 187000

Model: UDC-RDS

Description: UDC-RDS Internal Clock Delay

Simulator

External Clock Version

PT# 188000

Model: UDC-RDS_ECO

Description: UDC-RDS_ECO External Clock Delay

Simulator


INCLUDED WITH EACH UNIT:

- 1) Operations Manual
- 2) U.S.A. Grounded Power Cord, Part # 713015
- Optional Power Cords
 - A) United Kingdom, Part # 713016
 - B) Continental Europe, Part # 713017
 - C) Other: Specify Country on Purchase Order

Interfaces Available

Part No: 129014 RS-232 DCE I/M
Part No: 129032 RS-232 DTE I/M
Part No: 129010 V.35 DCE I/M
Part No: 129028 V.35 DTE I/M
Part No: 129011 RS-530 DCE I/M
Part No: 129029 RS-530 DTE I/M
Part No: 129012 RS-422 DCE I/M
Part No: 129030 RS-422 DTE I/M
Part No: 129013 X.21 DCE I/M
Part No: 129031 X.21 DTE I/M
Part No: 129057 TTL I/M

For further detailed technical information on this product, contact East Coast Datacom Technical Assistance toll free at (800) 240-7948



EAST COAST DATACOM, INC.

245 Gus Hipp Boulevard, STE 3 • Rockledge, FL 32955-4812 U.S.A.

TEL: (321) 637-9922 WEB SITE: www.ecdata.com FAX: (321) 637-9980