## **Power Blade**

## **High Density Power Distribution Unit**

Power up to 24 x 12V Data Center Appliances



## **Description and features**

The Power Blade is Profitap's solution for organized and efficient powering of 12V data center appliances. The Power Blade optimizes power outlet utilization in your data center by converting 2 power outlets into 24, enabling an organized cabling infrastructure with direct powering of up to 24 x 12V DC data center appliances from a 1U rackspace.

The double power supply setup makes for a fully redundant system, decreasing the risk of unexpected interruptions and costly downtime.

The Power Blade is available in 100–240V AC and -48V DC and outputs 24 x 12V DC to Molex Micro-Fit connectors. Two power supplies (AC or DC) and 24 Molex Micro-Fit to DC Jack cables are included with the Power Blade.

Power Blade offers a redundant powering solution with no hassle cable management for an organized cabling infrastructure in your data center.

- Redundant AC or DC input
- 24 x 12V DC output
- Platinum efficiency
- 750 W redundant powering
- Separate output power circuits
- 300 BTU/h
- Real-time fault detection
- Up to 2.5 A per output

## **Product specifications**

|                         | AC Power Blade                           | DC Power Blade                           |
|-------------------------|--|--|
| Connectors              | 24 x 12V DC Molex Micro-Fit              | 24 x 12V DC Molex Micro-Fit              |
|                         | 2 x 100-240V AC C14                      | 2x 36-72V DC screw terminal              |
| LEDs                    | 1 x General Status                       | 1 x General Status                       |
|                         | 2 x PSU Status                           | 2 x PSU Status                           |
|                         | 24 x Output Status                       | 24 x Output Status                       |
| Footprint               | 1U                                       | 1U                                       |
| Dimensions (WxDxH)      | 434 x 303 x 44 mm                        | 434 x 303 x 44 mm                        |
|                         | 17.09 x 11.93 x 1.73 in                  | 17.09 x 11.93 x 1.73 in                  |
| Weight                  | 5.4 kg                                   | 5.4 kg                                   |
|                         | 11.91 lb                                 | 11.91 lb                                 |
| Accessories<br>included | 2 x C13 cable                            | -  |
|                         | 24 x Molex Micro-Fit to DC<br>Jack cable | 24 x Molex Micro-Fit to DC<br>Jack cable |
| Compliance              | RoHS                                     | RoHS                                     |
|                         | CE                                       | CE                                       |
| Order Reference         | PWR1U-AC                                 | PWR1U-DC                                 |

PROFI**tap** 

