

CX42

DMM for the Outside Plant



The CX42 is a budget friendly and ultra portable telecom grade Digital Multimeter suitable for the Outside Plant.

Key Features

- DC Voltage measurement for line and equipment power verification and foreign voltage detection
- AC Voltage measurement for induced foreign voltage detection
- Resistance measurements for cable insulation verification and short detection
- DC and AC Current
- Capacitance measurements for verifying cable balance
- Simple user interface that saves time on the job

Specifications

- DC Voltage Range: 300V; Accuracy 2%, $\pm 1V$
- AC Voltage Range: 250V; Accuracy 2%, $\pm 1V$
- Resistance: 0Ω to 999 M Ω ; Accuracy 3%, $\pm 1\Omega$
- AC Loop Current Range: 80 mA; Accuracy 2%, ± 1 mA
- DC Loop Current Range: 110 mA; Accuracy 2%, ± 1 mA
- Capacitance Range: 1 μF ; Accuracy 3%, ± 1 nF
- Dimensions: 129 x 61 x 39 mm (5.1 x 2.4 x 1.5 in)
- Weight: <450 grams (<1 pound)
- Battery Options: Standard Alkaline AA or optional rechargeable NiMH
- Test Port: 2 mm banana



VeEX Inc.
2827 Lakeview Court
Fremont, CA 94538 USA
Tel: +1.510.651.0500
Fax: +1.510.651.0505
www.veexinc.com
customer@veexinc.com

© 2020 VeEX Inc. All rights reserved.
VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.
D05-00-184P A00 2020/11