

MPO Optical Power Meter - 12/24 Fiber



..... Wavelengths 850, 1310, 1550 nm

..... 4, 8, 12 or 24 fiber capable

..... Handheld, lightweight, long battery life

..... **APPLICATIONS:** FTTx, RFoG, EPoN, Intrafacility Cables

features:

- Two model: 12 or 24 Fiber
- Quick power measurement on all fibers
- Compact size, one button operation
- Color LCD for graph display
- Light weight for easy field use
- Quick start: No warm-up and 2 second measurement
- Software provided for data management

specifications :

Channels	12 or 24 Fiber
Wavelength	850, 1310, 1550 nm
Measurement Speed	<1.0 sec.
Measurement Range	+10 dBm to -40 dBm
Measurement Accuracy	±0.5 @ -20 dBm
Display Resolution	0.01 dB
Optical Connector	MPO Angled, unpinned
Display Units	dB, dBm
Display	2.8" TFT-LCD, 16 bit Color
Battery / Power	Rechargeable Lithium-Polymer – 7 hr.
Operating Temperature	-20° ~ +55° C
Weight	13 oz*
Dimensions h / w / d	6.75 x 3.5 x 1.5 inches*
	*w/ boot

ordering information

PPI-OPM-MPO12 12 fiber MPO Power Meter, APC, +10 dBm to -40 dBm
PPI-OPM-MPO24 24 fiber MPO Power Meter, APC,+10 dBm to -40 dBm
CO-CASE Protective hard case